


# D1100 digital preamplifier

- The D1100 digital preamplifier is a reference level stereo preamplifier and digital-to-analog converter (DAC) that supports all the latest high resolution file formats.
- It features the most advanced DAC we've ever used and delivers an unprecedented level of performance so that all your digital music is reproduced with exceptional accuracy and authenticity.
- Nine inputs are included to keep even the largest digital system connected. Three sets of balanced and unbalanced stereo outputs (one set fixed volume, two sets variable volume) connect the D1100 to your system.
- The D1100 is a full featured, fully functional self-contained unit that can be used independently of any other preamplifier. But thanks to McIntosh's engineering prowess, it can also be connected to and used in tandem with its analog equivalent, the C1100 Vacuum Tube Preamplifier.
- Audio channels and power supplies are electrically isolated from each other to produce true dual mono operation.
- Built from same polished stainless steel and hairline brushed black Titanium stainless steel as the C1100.



D1100 (left) shown with optional C1100. All units sold separately.



## Reference Level Digital Preamplifier and DAC

# McIntosh®

LEGENDARY PERFORMANCE™

[www.mcintoshlabs.com](http://www.mcintoshlabs.com)

# D1100 digital preamplifier



D1100 (bottom) shown with optional C1100. All units sold separately.



**Frequency Response:**  
+/-0.5dB from 4Hz to 20kHz  
+0.5/-3dB from 4Hz to 68kHz

**Total Harmonic Distortion:**  
0.0015%

**Signal to Noise Ratio:**  
111dB


**Rated Output Voltage  
(Unbalanced/Balanced):**  
Fixed: 2.0 Vrms/4.0 Vrms  
Variable: 0-8 Vrms/0-16 Vrms

**Digital Section:**  
3 optical, 3 coaxial, 1 MCT & 1 AES/EBU inputs decode digital music at up to 24-bit/192kHz; 1 USB input accepts PCM signals up to 32-bit/384kHz and supports DSD64, DSD128 and DSD256 plus DXD 352.8kHz and DXD 384kHz

**Overall Dimensions (W x H x D):**  
17-1/2" (44.45cm) x 6" (15.2cm) including feet x 19" (48.3cm)

**Weight:**  
26 lbs (11.8kg) net,  
41 lbs (18.6kg) in shipping carton

**For the Consumer's Protection:** In order to ensure the highest level of customer satisfaction, new McIntosh products may only be purchased from an Authorized McIntosh Dealer; and, with certain limited exceptions may only be purchased over-the-counter or delivered and installed by the Authorized McIntosh Dealer. McIntosh does not warrant, in any way, products that are purchased from anyone who is not an Authorized McIntosh Dealer, or that have had their serial numbers altered or defaced.



## Companion Products

The MC2KW Amplifier, C1100 Vacuum Tube Preamplifier, MCT450 SACD/CD Transport, MB100 Media Bridge, MB50 Streaming Audio Player, MEN220 Room Correction System, MPC1500 Power Controller and XRT2K Loudspeakers are logical companions for the D1100 Digital Preamplifier. Your Authorized Dealer can provide additional information on other McIntosh product combinations.

To learn more, please call us at 1.800.538.6576.

# McIntosh®

LEGENDARY PERFORMANCE™

www.mcintoshlabs.com